

Rustik (6 mm)



Description

Colourful natural stones encapsulated in a clear epoxy resin to produce an attractive slip-resistant floor finish.

Uses

Ideal for use in car showrooms, retail stores, conservatories, atriums, reception halls, conference zones, use limited only by your imagination.


Benefits

- Attractive natural stone finish
- Rapid installation
- Solvent free
- Abrasion resistant
- High chemical resistance
- Noise reduction (footsteps)
- Wear resistant
- Can be applied to most substrates

Project References

Wallis Stores, UK; Toyota, Ford, Peugeot, Audi, Volkswagen, Vauxhall and Saab car showrooms throughout Europe.

System Design



Standard Colour Chart



Wheatfield



Sand Dune



Coral Tree



Red Wood



Palm Leaf



Deep Fir

The colours and sizes of the applied aggregates may differ slightly from the examples shown above due to the use of natural stones.
Contact our customer services for a true colour sample or a special colour match.

Model Specification

Product: Rustik

Finish: Natural stone

Thickness: 6 mm

Colour: _____

Preparatory work and application in accordance with manufacturer's instructions.

Manufacturer: Flowcrete Asia Sdn. Bhd.

Telephone: Customer Service - + 603 6277 9575

Substrate Requirements

Concrete or screed substrate should be a minimum of 25 N/mm², free from laitance, dust and other contamination. The substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure. To produce the required aesthetic effect a smooth, level substrate is required. Contact Flowcrete for more advice.

Products Included in this System

Flowprime

Silica sand (16-30 Mesh)

Rustik

Detailed application instructions are available upon request.

Installation Service

The installation should be carried out by a Flowcrete approved applicator with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our web site at www.flowcrete.com.my.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Focus on the Floorzone

Flowcrete Asia Sdn Bhd is a division of the Flowcrete Group, world leaders in specialist industrial and commercial flooring. Systems available include: underfloor heating systems, floor screeds, surface damp proof membranes, decorative floor finishes, seamless terrazzo, car park deck waterproofing and corrosion protection systems... to name just a few. Our corporate objective is to satisfy your flooring needs.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

Fire Resistance	Class G. Certificate No 1721/75 SITAC
Slip Resistance	TRRL Pendulum Slip Test Dry >40 Wet 36
Abrasion Resistance BS8204:Part 2:2002	Class AR2 – Medium duty industrial and commercial
Temperature Resistance	Tolerant of sustained temperatures up to 60 °C
Chemical Resistance	Contact Technical Department
Compressive Strength	>30 N/mm ² (BS6319)
Flexural Strength	10 N/mm ² (BS6319)
Bond Strength	Greater than cohesive strength of 25 N/mm ² concrete. >1.5 MPa
Toxicity	Taint free to sensitive foodstuffs

Speed of Cure

	10°C	20°C	30°C
Light traffic	36 hrs	24 hrs	16 hrs
Full traffic	72 hrs	48 hrs	36 hrs
Full chemical cure	12 days	7 days	6 days

Aftercare - Cleaning and Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.

Flowcrete Asia Sdn Bhd (366254-X)
The Flooring Technology Centre
Lot 37631 & 37632, Jalan 6/37A,
Taman Bukit Maluri,
Industrial Area Kepong,
52100 Kuala Lumpur, Malaysia.
Tel: +(603) 6277 9575
Fax: +(603) 6277 4645
Email: malaysia@flowcrete.com
Flowcrete Asia is an RPM company

Flowcrete Thailand
522/41, Baan Klang Muang 1,
Soi Sahakampramoon,
Pracha-Uthit Road,
Wangthonglang, Bangkok, 10310.
Tel: (662) 2530 9611
Fax: (662) 2530 9610

E-mail: thailand@flowcrete.com

Flowcrete Indonesia
2nd Floor, Suite 203,
Palma One Building,
Jl. HR Rasuna Said Kav. X2 No. 4
Jakarta Selatan 12950, Indonesia.
Tel: +6221 252 3201
Fax: +6221 252 0720

E-mail: indonesia@flowcrete.com

Flowcrete Vietnam
Representative Office
3rd Floor, 130 Nguyen Cong Tru Street,
Nguyen Thai Binh Ward,
District 1, HCMC, Vietnam
Tel: +848 3821 6561
Fax: +848 3821 6501

E-mail: vietnam@flowcrete.com